



Windsor Series Plate Steel Wood Burning Stoves and Inserts

MAJESTIC 

Add the traditional look and warmth of a stove to any room with our wide selection of wood burning stoves from Majestic. These wood burning stoves combine the heritage appeal of fine craftsmanship with the convenience of contemporary wood burning technology to ensure optimal functionality and timeless beauty.

THE WINDSOR SERIES PLATE STEEL WOOD BURNING STOVES

PREMIUM STEEL – CAST STOVES

Style and performance – heavy 5/16" thick top; firebrick firebox lining, cast-iron door, air hood, ash lip, and base elements. Three sizes. All models include convenient ash drawer. All cast iron components are made in our Vermont foundry. Polished nickel handle to match today's interior finishes. Convective side panels reduce side clearances. Three sizes: Small (1,000 sq. ft): WR1000L02, Medium (1,500 sq. ft): WR1500L02, Large (2,000 sq. ft): WR2000L02

WR1500L02 plate steel wood stove with black cast iron legs shown on cover



WR1500L02 Plate steel wood burning stove with Black cast iron legs

Give people a place to gather – make fire the focal point of your room again with a plate steel wood burning stove or insert from Majestic.



WR2500X02 Plate steel wood burning insert

THE WINDSOR PLATE STEEL WOOD BURNING INSERT

Crafted with the same sturdy construction as our wood stoves, this masonry wood insert is designed for existing masonry fireplaces. Standard features include a brick-lined firebox, blower, and faceplate (44 1/8" W x 31" H) with nickel trim. Heating capacity up to 1,500 sq. ft.

VALUE LINE OF STEEL STOVES

Durable and rich at a value price. Stylish rolled top adds durability without adding unnecessary bulk—3/16" thick top has strength of 5/16" flat top. Cast iron doors provide a large ceramic glass viewing area. Air wash design helps maintain a clean glass. Firebrick firebox lining.

MOBILE HOME APPROVED WOOD STOVE MODEL WR247001

- Heating capacity up to 1,000 sq. ft.
- HUD approved for use in mobile homes; outside air connection
- Reduced clearance convection side panels

SMALL STEEL WOOD STOVE MODEL WR244

- Heating capacity up to 1,000 sq. ft.
- Features cast iron door with steel legs

MEDIUM STEEL WOOD STOVE MODEL WR270007

- Heating capacity up to 1,500 sq. ft.
- Features pedestal base with ash drawer

LARGE STEEL WOOD STOVE MODEL WR300007

- Heating capacity up to 2,000 sq. ft.
- Features pedestal base with ash drawer



WR247001 Mobile home approved wood burning stove



WR244 Small steel wood burning stove



WR270007 Medium steel wood burning stove



WR300007 Large steel wood burning stove

The Windsor Series Plate Steel Wood Burning Stoves and Inserts

Model	WR247001 Flat top with pedestal Mobile home approved	WR244 Flat top with legs	WR270007 Flat top with pedestal	WR300007 Flat top with pedestal	WR1000L02 Step top with legs	WR1500L02 Step top with legs	WR2000L02 Step top with legs
Heated Area*	up to 1,000	up to 1,000	up to 1,500	up to 2,000	up to 1,000	up to 1,500	up to 2,000
EPA Burn Rate (BTU/hr)	11,492-18,920	10,467-26,100	10,370-29,301	11,800-32,300	10,467-26,100	10,370-29,301	11,800-32,300
Avg. Efficiency %	65.3	74.5	63.0	63.0	74.5	63.0	63.0
EPA Emissions g/hr.	5.0	5.3	4.4	2.7	5.3	4.4	2.7
Firebox Vol. cu. ft.	1.2	1.3	1.5	2.15	1.3	1.5	2.15
Log Length	18"	18"	22"	20"	18"	22"	20"
Stove Wt. lbs.	180	180	310	300	222	350	350
Shipping Wt. lbs.	210	210	330	320	270	380	385
Flue collar size	6"	6"	6"	6"	6"	6"	6"
Over-all Dims.	31 3/4" h 22 3/4" w 20 3/8" d	26 15/16" h 22 1/2" w 20 5/8" d	29 9/16" h 27" w 20 7/8" d	31 1/2" h 26 1/2" w 25 1/8" d	27" h 23 3/4" w 20 1/2" d	30" h 28 1/4" w 22 1/4" d	31" h 26 1/2" w 26" d
Ash Drawer	NO	NO	YES	YES	YES	YES	YES
Clearance to Combustibles	Top	54"	56"	54 1/2"	54"	56"	54"
	Single Wall	10 1/2"	15"	13"	10"	12 1/2"	9"
	Rear Sides	10 1/2"	18"	17 1/2"	15"	12"	11 1/2"
	Pipe Corner	10 1/2"	7"	11"	9"	7"	9"
Clearance to Combustibles	Double Wall	5"	N/A	N/A	N/A	8"	6"
	Rear Sides	2 1/2"	N/A	N/A	N/A	8 1/2"	6"
	Pipe Corner	2 1/2"	N/A	N/A	N/A	5 1/2"	4"

Model	WR2500X02								
Heat Area Sq. ft*	EPA Burn Rate (BTU/hr)	Avg. Efficiency %	EPA Emissions g/hr	Firebox Vol. cu. ft.	Flue Collar size	Log Length	Product Wt. lbs.	Insert Dim.	Min. Fireplace Opening
up to 1,500	9,600-58,000	64%	4.7	1.3	6"	20"	250 26 3/4" w 20 3/4" d	21 3/4" h 30 3/4" w 10" d Faceplate: 31" h x 44" w	23 3/4" h

See our owners manual for complete dimensions and installation specifications. Units require 6" diameter flue connector.

*Note: Actual heating area will vary based on fuel, home construction and region.

For more information about MHSC and Majestic efficient and environmentally friendly products, please visit www.majesticproducts.com



MAJESTIC

A Brand of Monessen Hearth Systems Co.
149 Cleveland Drive, Paris, Kentucky 40361
www.majesticproducts.com

Your Majestic Dealer:

To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2010 Monessen Hearth Systems Co.